



PAGE 1 of 11	<b>BASE METALS REFINERY</b> 
REVISION N°.: 20 ORIGINAL DATE ISSUED : <27-JUN-2005 LAST REVIEWED: 24-Aug-2020	<b>SAFETY DATA SHEET – NICKEL POWDER</b> DOCUMENT N°.: <b>MAN-HDS-003</b>

**DISTRIBUTION CONTROL SHEET**

COPY N°	LOCATION	TITLE
1	Quality Offices	Document Controller
2	SHEQ	SHEQ Manager (Electronic)
3	SHEQ	SHE Manager (Electronic)
4	Despatch	Process Supervisor (Electronic)
5	Plant Manager’s Office	Plant Manager – Nickel (Electronic)
6	Manager – BMR Office	Manager – BMR (Electronic)
7	Lab. Manager’s Office	Laboratory Manager (Electronic)
8	Marketing	Marketing & Refineries’ Executive Manager (Electronic)
9	Marketing & Sales	Base Metals Sales Manager (Electronic)
10	IRS	IRS Contracts Manager (Electronic)
11	Alice Lourens	Manager Investor Relations (for inclusion on Implats’ Web Page)

PAGE 2 of 11	<p style="text-align: center;"><b>BASE METALS REFINERY</b></p> 
REVISION N <sup>o</sup> .: 20 LAST REVIEWED : 24-Aug-2020	<p style="text-align: center;"><b>SAFETY DATA SHEET – NICKEL POWDER</b></p> DOCUMENT N <sup>o</sup> .: <b>MAN-HDS-003</b>

**1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER**

**1.1 Product identifier**

**Product Name**                      Nickel Powder

**Synonym(s)**                        Nickel Metal Powder, 994 Nickel Powder, Impala Nickel Powder

**1.2 Uses and uses advised against**

**Use(s)**                                  Catalyst, Printing Industry, Metal Alloys, Nickel Plating, Ceramic Manufacture, Process Chemical, Industrial Application, Steel Manufacturing.

**1.3 Details of the supplier of the safety data sheet**

**Supplier name**                      Impala Platinum Ltd – Refineries

**Address**                                Base Metals Refinery  
 P.O. Box 222  
 SPRINGS  
 1560  
 GAUTENG  
 Republic of South Africa

**Contact Person(s)**                Laboratory Manager, BMR – Suzanne Finney  
 Tel: +27 11 3603478  
 E-mail: [suzanne.finney@implats.co.za](mailto:suzanne.finney@implats.co.za)

    Nickel Manager, BMR – Sakhumzi Ndlebe  
 Tel: +27 11 3603317  
 E-mail: [Sakhumzi.ndlebe@implats.co.za](mailto:Sakhumzi.ndlebe@implats.co.za)

**1.4 Emergency Contact telephone number(s)**

For emergency information – see above for Impala Platinum contacts.  
 South Africa Poisons Information Centre: (24 hours): 0861 555 777 (South Africa only)

**2. HAZARDS IDENTIFICATION**

**2.1 Classification of the substance or mixture**

CLASSIFIED AS HAZARDOUS ACCORDING TO SANS 10234

<b>GHS Classification(s)</b>	Acute toxicity, oral	Category 4
	Respiratory sensitisation	Category 1
	Skin sensitisation	Category 1
	Carcinogenicity	Category 2
	Specific target organ Toxicity (RE)	Category 1
	Aquatic toxicity (Chronic)	Category 3

Page 3 of 11	Document N <sup>o</sup> .:MAN-HDS-003	<b>BASE METALS REFINERY</b>
Revision N <sup>o</sup> .: 20 Last Reviewed: 24-Aug-2020	<b>SAFETY DATA SHEET – NICKEL POWDER</b>	

**2.2 Label Elements:**  
**Signal Word**

DANGER

**Hazard Pictograms**



**Health Statement(s)**

- H301 Harmful if swallowed
- H317 May cause an allergic skin reaction
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled
- H413 May cause long lasting harmful effects to aquatic life
- H351 Limited evidence of carcinogenic effect
- H372 Causes damage to organs through prolonged or repeated exposure

**Prevention statement(s)**

- P201 Obtain special instruction before use
- P202 Do not handle until all safety precautions have been read and understood
- P261 Avoid breathing dust/fume
- P264 Wash thoroughly after handling
- P270 Do not eat, drink or smoke when using this product
- P272 Contaminated work clothes must not be allowed out of the work place
- P273 Avoid release to the environment
- P280 Wear protective gloves, protective clothing and eye protection
- P285 In case of inadequate ventilation wear respiratory protection

**Response statements(s)**

- P330 Rinse mouth
- P101 + P312 IF SWALLOWED: Call a poison centre/doctor
- P302 + P352 IF ON SKIN: Wash well with plenty of soap and water
- P304 + P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
- P308 + P313 If exposed or concerned get medical advice/attention
- P311 + P342 If experiencing respiratory symptoms call a poison centre or doctor
- P321 Specific treatment is advised – see first aid instructions
- P333 + P313 If skin irritation or rash occurs get medical advice/attention
- P337 + P313 If eye irritation persists get medical advice/attention
- P363 Wash contaminated clothing before reuse

**Storage statement(s)**

- P405 Stored locked up

**Disposal statement(s)**

- P501 Dispose of contents/container in accordance with relevant regulations

Page 4 of 11	Document N <sup>o</sup> .:MAN-HDS-003	<b>BASE METALS REFINERY</b>
Revision N <sup>o</sup> .: 20 Last Reviewed: 24-Aug-2020	<b>SAFETY DATA SHEET – NICKEL POWDER</b>	

**2.3 Other Hazards:**  
No information provided

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

**3.1 Substances/Mixtures**

<b>Ingredient</b>	Nickel
<b>Formula</b>	Ni
<b>CAS #</b>	7440-02-0
<b>Poison Sched.</b>	None Allocated
<b>Conc. Ni</b>	≥99.80%
<b>Conc. Co</b>	<0.15%
<b>RTECS #</b>	QR5950000
<b>EC #</b>	231-111-4
<b>ICSC #</b>	0062
<b>Hazchem.</b>	None Allocated
<b>UN #</b>	None Allocated
<b>D.G Class</b>	None Allocated
<b>PKG Group</b>	None Allocated
<b>EPG</b>	None Allocated
<b>Sub/Tert. Risk</b>	None Allocated

**4. FIRST AID MEASURES**

**4.1 Description of first aid measures**

<b>Eye</b>	Flush gently with running water for minimum 15 minutes. Seek medical attention if irritation develops.
<b>Inhalation</b>	If over exposure occurs leave exposure area immediately. If other than minor symptoms are displayed seek immediate medical attention. Apply artificial respiration if not breathing.
<b>Skin</b>	Remove contaminated clothing and gently flush affected areas with soap and water. Seek medical attention if irritation develops. Launder clothing before reuse. Maintain good personal hygiene.
<b>Ingestion</b>	If poisoning occurs, contact a Doctor or South Africa Poisons Information Centre (24 hours): 0861-555-777 (South Africa only). Do not induce vomiting. Seek immediate medical attention.

**First Aid Facilities** Eye wash and safety shower facilities should be available.

**4.2 Most important symptoms and effects, both acute and delayed**

Symptoms and effects are generally associated with chronic exposure (i.e. lung fibrosis). May cause an allergic skin reaction. May cause allergy or asthma or breathing difficulties if inhaled.

**4.3 Immediate medical attention and special treatment needed**

Treat symptomatically.

**5. FIRE FIGHTING MEASURES**

**5.1 Extinguishing Media**

Use an extinguishing agent suitable for a surrounding fire.

Page 5 of 11	Document N <sup>o</sup> .:MAN-HDS-003	<b>BASE METALS REFINERY</b>
Revision N <sup>o</sup> .: 20 Last Reviewed: 24-Aug-2020	<b>SAFETY DATA SHEET – NICKEL POWDER</b>	

**5.2 Special hazards arising from the substance or mixture**

Non-flammable. May evolve toxic nickel oxides when heated. Very finely divided nickel metal in the fully reduced state can smoulder in the presence of oxygen or air. Fine dust may be explosive at high concentrations and/or in confined areas. Prevent contamination of drains or waterways; absorb runoff with sand or similar (**NOT** carbon dioxide or water).

**5.3 Advice for firefighters**

Evacuate area and contact emergency services. Remain upwind and notify those downwind of hazard. Wear full protective equipment (see spillage section 6.1 below) including Self Contained Breathing Apparatus (SCBA) when combating fire. Use water fog to cool intact containers and nearby storage areas.

**5.4 Hazardous Chemical Code**

None allocated.

**6. ACCIDENTAL RELEASE MEASURES**

**6.1 Personal precautions, protective equipment and emergency procedures**

Wear PPE as detailed in section 8 of this SDS.

**6.2 Environmental precautions**

Prevent product from entering drains and waterways.

**6.3 Methods of cleaning up**

Contain spillage, and collect and place in suitable containers for disposal. Avoid generating dust.

**6.4 References to other sections**

See sections 8 and 13 for exposure controls and disposal

**7. HANDLING AND STORAGE**

**7.1 Precautions for safe handling**

Before use, read the product label. Use safe work practices to avoid eye or skin contact and inhalation. Observe good personal hygiene. Prohibit eating, drinking and smoking in contaminated areas (e.g. if container is damaged). Wash hands before eating or smoking.

**7.2 Conditions for safe storage, including any incompatibilities**

Store in cool, dry, well ventilated area, removed from oxidising agents (e.g. hypochlorites), acids (sulfuric acid), heat sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Large storage areas should have appropriate ventilation systems.

**7.3 Specific end use(s)**

Packed in brown 250kg drums and loaded in 1000kg lots on a pallet. Each drum sealed with a security seal.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**8.1 Control parameters**

<b>Exposure standards</b>	SA Legislation	Ni soluble = 0.1 mg/m <sup>3</sup> Ni insoluble = 0.5 mg/m <sup>3</sup> Ni metal = 0.5 mg/m <sup>3</sup>
	ICSC0062	Ni soluble = 0.1 mg/m <sup>3</sup> Ni insoluble = 0.2 mg/m <sup>3</sup> Ni metal = 1.5 mg/m <sup>3</sup>
	SWA (AUS)	Ni Metal TWA 1 mg / m <sup>3</sup> Ni Soluble compounds (as Ni): TWA 0.1mg / m <sup>3</sup>
<b>Biological Limits</b>	No biological limit allocated for nickel	

Page 6 of 11	Document N <sup>o</sup> .:MAN-HDS-003	<b>BASE METALS REFINERY</b>
Revision N <sup>o</sup> .: 20 Last Reviewed: 24-Aug-2020	<b>SAFETY DATA SHEET – NICKEL POWDER</b>	

**8.2 Exposure Controls**

**Engineering controls** Do not inhale dust / powder. Use with adequate natural ventilation. Where a dust inhalation hazard exists, mechanical extraction ventilation is recommended. Maintain dust / fume levels below the recommended exposure standard.

**PPE**

<b>Eye</b>	Wear dust-proof goggles
<b>Hand</b>	Wear PVC or rubber gloves.
<b>Body</b>	Wear overalls. Do not take working clothes home.
<b>Respiratory</b>	Where an inhalation risk exists, wear a Class P2 (Particulate) respirator.

**9. PHYSICAL AND CHEMICAL PROPERTIES****9.1 Information on basic physical and chemical properties**

<b>Appearance</b>	Grey/Silver Powder
<b>Odour</b>	Odourless
<b>Flammability</b>	Non Flammable
<b>Flash Point</b>	Not Relevant
<b>Lower Explosion Limit</b>	Not Relevant
<b>Upper Explosion Limit</b>	Not Relevant
<b>Auto Ignition Temperature</b>	Not Available
<b>Decomposition Temperature</b>	Not Available
<b>Boiling Point</b>	2730 °C
<b>Melting Point</b>	1455 °C
<b>Evaporation Rate</b>	Not Relevant
<b>pH</b>	Not Relevant
<b>%Volatiles</b>	Not Relevant
<b>Vapour Density</b>	Not Available
<b>Specific Gravity</b>	8.90
<b>Vapour Pressure</b>	Not Relevant
<b>Solubility (water)</b>	Insoluble
<b>Partition Coefficient</b>	Not Available
<b>Viscosity</b>	Not Relevant
<b>Explosive Properties</b>	Not Available
<b>Oxidising Properties</b>	Not Available
<b>Odour Threshold</b>	Not Available
<b>Molecular Weight</b>	58.71g/mole
<b>Ni concentration</b>	≥99.80%

**9.2 Other information**

No other information available.

**10. STABILITY AND REACTIVITY****10.1 Reactivity**

Carefully review all information in sections 10.2 to 10.6.

**10.2 Chemical stability**

Stable under recommended conditions of storage

**10.3 Possibility of hazardous reactions**

No reactions expected, except if exposed to incompatible materials – see section 10.5

**10.4 Conditions to avoid**

Avoid heat, sparks, open flames and other ignition sources (fine particles, <3µm, can combust when exposed to ignition sources), as well as incompatible materials (section 10.5)

Page 7 of 11	Document N <sup>o</sup> .:MAN-HDS-003	<b>BASE METALS REFINERY</b>
Revision N <sup>o</sup> .: 20 Last Reviewed: 24-Aug-2020	<b>SAFETY DATA SHEET – NICKEL POWDER</b>	

**10.5 Incompatible materials**

May evolve flammable – explosive hydrogen gas in contact with strong acids. Incompatible with oxidising agents (e.g. hypochlorites, peroxide, ammonium nitrate) and acids (e.g. sulfuric acid, hydrochloric acid) reacts slowly with non-oxidising acids and more rapidly with oxidising acids. Also incompatible with nitrates, sulfur, selenium, Halogens, Halogen-Halogen Compounds, nitril compounds and organic solvents. Reacts violently in powder form with titanium powder and potassium perchlorate.

**10.6 Hazardous decomposition products**

Will evolve toxic metal oxides when heated to decomposition.

**11. TOXICOLOGICAL INFORMATION****11.1 Information on toxicological effects**

**Acute Toxicity** No reliable data available for nickel. LD50 (Ingestion) for rat is expected to be >9 000mg/kg

**Skin** Slightly corrosive – irritant. Repeated contact may result in irritation, dermatitis with severe itching and possible sensitisation. A skin sensitiser. “Nickel itch” may begin with a burning and itching sensation, followed by redness and blister. Once acquired, nickel sensitivity usually persists. Nickel and its compounds can be absorbed through the skin, but not in amounts sufficient to cause intoxication. Individuals with pre-existing lung or skin sensitivities/diseases are advised to avoid exposure.

**Eye** Irritant. Contact may result in lacrimation, irritation, pain redness and conjunctivitis. Prolonged contact – corneal burns and possible permanent damage.

**Mutagenicity** Insufficient data available to classify as a mutagen.

**Carcinogenicity** Nickel metal is allocated a GHS Classification of “Category 2 - Suspected Carcinogen”. Nickel, metallic and alloys are classified as possibly carcinogenic to humans) IARC Group 2B). These classifications are based on the lack of human evidence of carcinogenicity, but the presence of positive results for tumour induction in animals after injection or intratracheal instillation. An animal inhalation study was negative for carcinogenicity (Oller et al. 2008).

**Reproductive** Insufficient data available to classify as a reproductive or development toxin.

**STOT – SE** No relevant or reliable studies available. Ingestion may result in gastric irritation, ulceration and burns to the mouth and throat with nausea, vomiting and abdominal pain. Nickel is poorly absorbed through the stomach.

**STOT - RE** Over exposure to dust may result in respiratory mucous membrane irritation and sensitisation. Early inhalation symptoms include nausea, giddiness, weakness, and non-productive cough, followed by breathing difficulties, pulmonary oedema and interstitial fibrosis. Half-life in the body: 667 days. Chronic exposure to nickel compounds may result in increased incidence of asthma and decreased pulmonary function.

Nickel salts have been shown to cause an increased incidence of asthma and bronchitis, decreased pulmonary function.

Nickel is poorly absorbed through the gastrointestinal tract, which accounts for its low toxicity via this route. Large doses, 1-3 mg/kg of nickel compounds have been reported to cause intestinal disorders, convulsions & asphyxia in dogs. Heart, brain, liver and kidney damage reported in animals.

Page 8 of 11	Document N <sup>o</sup> .:MAN-HDS-003	<b>BASE METALS REFINERY</b>
Revision N <sup>o</sup> .: 20 Last Reviewed: 24-Aug-2020	<b>SAFETY DATA SHEET – NICKEL POWDER</b>	

**Aspiration** Not relevant.

**Sensitisation** Sufficient data from human studies exists to warrant classification of nickel as a dermal sensitiser via skin contact. The data availability is insufficient for classification of metallic nickel as a respiratory sensitiser.

**12. ECOLOGICAL INFORMATION**

**12.1 Toxicity**

Limited eco-toxicity data was available for this product at the time this report was prepared. Metallic nickel may be harmful to aquatic life with long lasting effects – Aquatic toxicity classification relates to particle sizes less than 1mm diameter (equivalent spherical diameter).

**12.2 Persistence and degradability**

Not applicable for inorganic substances.

**12.3 Bio accumulative potential**

No information available.

**12.4 Mobility in soil**

Nickel mobility in soil is dependent on many parameters, including pH, and naturally occurring silica and hydrous oxides of iron and manganese. Mobility of nickel is controlled by various sorbents which scavenge it from solution. In pristine environments, hydrous oxides of iron and manganese control its mobility via sorption and co-precipitation. In polluted environments, the most abundant organic material will keep nickel soluble. Nickel is one of the most mobile heavy elements in aquatic environments and can persist indefinitely in natural waters. It is toxic to plants at 50-200ppm. Avoid acid dissolution of the nickel metal.

**12.5 Results of PBT and vPvB assessment**

No information available.

**12.6 Other adverse effects**

Nickel and nickel compounds are currently being researched at an International level for eco-toxicity and ecological effects, including bioavailability, partitioning partitioning properties and mobility of the various chemical forms of nickel.

**13. DISPOSAL CONSIDERATION**

**13.1 Waste treatment methods**

**Waste Disposal** Collect and reuse where possible. Minimise dust generation. Contact Impala Refineries personnel for additional information – see section 1.3

**Legislation** Dispose of in accordance with relevant local legislation.

**14. TRANSPORT INFORMATION**

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG, IMDG OR IATA

	<b>Land Transport (ADG)</b>	<b>Sea Transport (IMDG/IMO)</b>	<b>Air Transport (IATA/ICAO)</b>
<b>14.1 UN #</b>	None Allocated	None Allocated	None Allocated
<b>14.2 UN proper shipping name</b>	None Allocated	None Allocated	None Allocated
<b>14.3 Transport hazard class</b>			
<b>D.G Class</b>	None Allocated	None Allocated	None Allocated
<b>Subsidiary risk(s)</b>	None Allocated	None Allocated	None Allocated

**AUTHORISED COPY**  
Before print ensure use of latest revision and destroy previous copies



Page 9 of 11	Document N <sup>o</sup> .:MAN-HDS-003	<b>BASE METALS REFINERY</b>
Revision N <sup>o</sup> .: 20 Last Reviewed: 24-Aug-2020	<b>SAFETY DATA SHEET – NICKEL POWDER</b>	

<b>14.4</b>	<b><u>Packing Group</u></b>	None Allocated	None Allocated	None Allocated
<b>14.5</b>	<b><u>Environmental hazards</u></b>	None Allocated	None Allocated	None Allocated
<b>14.6</b>	<b><u>Special precautions for user</u></b>			
	<b>Hazchem code</b>	None Allocated	None Allocated	None Allocated

**Other information** "Under US DOT only, DG 9, UN 3077 applies to nickel powders if they are < 100 micron in particle size, and if they are packaged in quantities greater than 100 pounds (0.05 metric tonne)".

## 15. REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

**Poison schedule** A poison schedule number has not been allocated to this product, using the criteria in SUSMP.

**Classifications**

N	Dangerous for the environment.
T	Toxic
Xi	Irritant

**Risk phrases**

R40	Limited evidence of carcinogenic effect
R43	May cause sensitisation by skin contact
R48/23	Toxic. Danger of serious damage to health by prolonged exposure through inhalation
R49	May cause cancer by inhalation
R53	May cause long term adverse effects in the aquatic environment

**Safety phrases**

S2	Keep out of reach of children
S22	Do not breathe dust
S24	Avoid contact with skin
S26	In case of contact with eyes rinse immediately in running water, and seek medical advice
S36/37/39	Wear suitable protective clothing, gloves, eye protection
S45	In case of accident or if you feel unwell, seek medical advice (show label where possible).
S61	Avoid release to the environment. Refer to the specific instructions in the SDS.

**Regulatory information** SA Hazardous Substances Act 15/1973

SANS 10228:2012 SA National Standard – The identification and classification of dangerous goods for transportation by road and rail modes

GHS of Classification and Labelling of Chemicals ST/SG/AC.10/3-/Rev.6

Regulation (EC) No. 1907/2006 of the European Parliament and the Council of December 2006

### 15.2 Chemical safety assessment

No other information available

Page 10 of 11	Document N <sup>o</sup> .:MAN-HDS-003	<b>BASE METALS REFINERY</b>
Revision N <sup>o</sup> .: 20 Last Reviewed: 24-Aug-2020	<b>SAFETY DATA SHEET – NICKEL POWDER</b>	

## 16. OTHER INFORMATION

### Additional information

**NICKEL EXPOSURE 1:** NIOSH-USA recommended that workers exposed to Nickel and inorganic nickel compounds should have an initial medical exam covering.

1. Comprehensive medical and work history with emphasis on skin conditions, allergies, upper and lower respiratory tract illnesses and smoking.
2. Complete physical exam with emphasis on upper respiratory tract and skin.
3. Specific clinical tests such as X-ray, pulmonary function and indicated sputum cytology and urine nickel analysis.

**NICKEL:** Reported and potential adverse health effects associated with occupational exposure to Nickel metal and inorganic compounds include; an increased risk of nasal, lung and possibly laryngeal cancer in nickel refinery workers; increased risk of gastric cancer; increased risk of sarcoma (cancer arising from connective tissue); severe irritation of the upper respiratory tract; pulmonary irritation and fibrosis; pneumoconiosis; bronchial asthma; increased susceptibility to respiratory infections; and dermatitis.

**RESPIRATORS:** In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

**HEALTH EFFECTS FROM EXPOSURE:** It should be noted that the effects from exposure to this will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a Chem Alert report which encompasses all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

**PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:** The recommendation for protective equipment contained within this Chem Alert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made. Additional technical information is available by calling +27 11 3603478 or +27 11 3603317.

**COLOUR RATING SYSTEM:** Amber. Chem Alert reports are assigned a colour rating of Green, Amber or Red for the purpose of providing users with a quick and easy means of determining the hazardous nature of a product. Safe handling recommendations are provided in all Chem Alert reports so as to clearly identify how users can control the hazards and thereby reduce the risk (or likelihood) of adverse effects. As a general guideline a Green colour rating indicates a low hazard, and Amber colour rating indicates a moderate hazard and a Red colour indicates rating indicates a high hazard.

Whilst all due care has been taken in the preparation of the Colour Rating System, it is intended as a guide only and does not provide any warranty in relation to the accuracy of the Colour Rating System. As far as is lawfully possible, Impala accepts no liability or responsibility whatsoever for the actions or omissions of any person in reliance on the Colour Rating System.

Page 11 of 11	Document N <sup>o</sup> .:MAN-HDS-003	<b>BASE METALS REFINERY</b>
Revision N <sup>o</sup> .: 20 Last Reviewed: 24-Aug-2020	<b>SAFETY DATA SHEET – NICKEL POWDER</b>	

**Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists.
mg/m <sup>3</sup>	Milligrams per cubic metre.
AUS	Australia
CAS #	Chemical Abstract Service number – used to uniquely identify chemical compounds.
CNS	Central Nervous System.
EC No.	European Commission Number
EMS	Emergency Schedules (Emergency procedures for ships carrying dangerous goods.
EU	European Union
GHS	Globally Harmonised System
IARC	International Agency for Research on Cancer.
*IATA	<i>International Air Traffic Association</i>
*ICAO	<i>International Civil Aviation Organisation</i>
ICSC	International Chemical Safety Card.
*IMDG	<i>Inter Modal transport of Dangerous Goods</i>
*IMO	<i>International Maritime Organisation</i>
LC50	lethal Concentration, 50%/ Median Lethal Concentration.
LD50	Lethal Dose, 50% / Median Lethal Dose.
M	Moles per litre, a unit of concentration.
OEL	Occupational Exposure Limit.
pH	Relates to hydrogen ion concentration - this value will relate to a scale of 0 – 14, where 0 is highly acidic and 14 is highly alkaline.
*PPE	<i>Personal Protective Equipment</i>
ppm	Parts Per Million.
RTECS	The Registry of Toxic Effects of Chemical Substances.
STEL	Short Term Exposure Limit
STOT-RE	Specific Target Organ Toxicity – repeated exposure
STOT-SE	Specific Target Organ Toxicity – single exposure
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA/ES	Time Weighted Average of Exposure Standard.

**Report Status:** Impala Platinum Ltd. have exercised reasonable care in the preparation of the information contained in this SDS, however, it assumes no responsibility or liability to the accuracy and suitability of such information, for application to the Buyer's intended purposes or consequences of its use. As regulatory standards and guideline recommendations are revised from time to time, Impala gives no assurance that the information contained in this SDS will be current at the time that the SDS is used. It is the responsibility of the Buyer/User to ensure that the most recent version of this document is available.

The data in this SDS relates only to the specific material designated herein and does not relate to use in combination with other materials and in any process. Impala assumes no responsibility for any physical or chemical changes, which the Buyer/User may make to the material designated in this SDS. Since use of this SDS information and the opinions and conditions of the use of the product are not within the control of Impala Platinum Ltd., the Buyer/User is obligated to determine the conditions of safe use of the product.